

Saint-Gobain API BV

Newtonweg 1
3846 BJ Harderwijk
The Netherlands

P.O. Box 1
3840 AA Harderwijk
The Netherlands
T +31 (0)341 474600
F +31 (0)341 474626
E sales@api.nl
www.api.nl

Chamber of Commerce
08015950
BTW NL004318894.B.01

Declaration of Performance 0007-175E

Quick-Lock Insula 38

1. Unique identification of product : Quick-Lock® Insula 38
2. Identification of the construction product components:
Quick-Lock 24-38, Insula 38 edge
3. Intended use: Suspension system components for ceilings in building interiors
4. Manufacturer: Saint-Gobain API BV Newtonweg 1 Harderwijk The Netherlands www.api.nl
5. Authorized representatives: n.a.
6. System of assessment and verification of performance:
 - 6.1. Loadbearing capacity: System 3
 - 6.2. Reaction to fire: System 3 or 4
 - 6.3. Durability: System 4
7. Harmonized standard covering the construction product- EN 13964-2007 suspended ceilings:
 - 7.1. Loadbearing capacity: Tests carried out by NB0432 MPA Dortmund; NB1153 TNO Delft
 - 7.2. Reaction to fire: Galvanized steel Commission decision 96/603/EC; Coil-coated steel Commission decision 2010/737/EC: Tests carried out by NB 0679 CSTB RA08-0251,
 - 7.3. Durability: EN 13964 Table 8
8. European Technical Assessment: n.a.

QUICK-LOCK®


Ceiling systems

9. Declared performances:

	7.1 Load bearing capacity					7.2 Reaction to fire	7.3 Durability
	Deflection	Span min/max mm	Admissible bending moment (M _{adm}) Nm	Maximum bending moment (M _u) Nm	Bending stiffness (EI) Nm ²		
Insula U-38 edge	Class 1	npd	npd	npd	npd		Class A1 Class B
QL 24-38 HE	Class 1	1000 / 1250	27,0	38,7		NB0432	Class A1 Class B

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performances point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer:



J. van Eekhout
Managing Director
Harderwijk, NL, 21-05-2013