

DECLARATION OF PERFORMANCE
No. 28_1117134_2019

1. Unique identification code of the product type:
RIGIPS PRO Fire+ type DF thickness: 18 mm
2. Intended use(s):
Gypsum plasterboard designed for use in construction works, including those designed for processing as part of further treatment
3. Manufacturer:
Saint-Gobain Construction Products Polska Sp. z o.o.
ul. Okrężna 16, 44-100 Gliwice
Manufacturing plant: **Rigips-Stawiany Factory**
Szarbków 73, 28-400 Pińczów
4. System or systems of assessment and verification of constancy of performance:
System 3
5. Harmonised standard: **EN 520:2004+A1:2009**
Notified body: **Building Research Institute (ITB), No. 1488**
6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Shear strength (for stiffening timber-framed external walls and timber roof truss structures)	NPD	EN 520:2004+A1:2009
Reaction to fire (for an uncovered product)	A2-s1,d0 (C2)	EN 520:2004+A1:2009
Water vapour permeability (for moisture diffusion control)	10 μ	EN 520:2004+A1:2009
Flexural strength longitudinal direction transverse direction	770 N 300 N	EN 520:2004+A1:2009
*Impact resistance (in end-use conditions)	NPD	EN 520:2004+A1:2009
*Airborne sound insulation (in end-use conditions)		
*Acoustic absorption (in end-use conditions)		
Thermal resistance (as thermal conductivity)	0.25 W/(mK)	EN 520:2004+A1:2009

* These properties depend on the system, and they are provided in the manufacturer's information at www.rigips.pl depending on the expected applications

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:
Michał Zakrzewski, Operational Director RIGIPS
(name and position)
Szarbków, 18.10.2019
(place and date of issue)


(signature)