



DECLARATION OF PERFORMANCE No. 22 1117127 2018

1. Unique identification code of the product type: RIGIPS PRO Fire+ Hydro type DFH2 thickness: 15 mm

2. Intended use(s):

Gypsum plasterboard designed for use in construction works, including those designed for processing as part of further treatment

3. Manufacturer:

Saint-Gobain Construction Products Polska Sp. z o.o. ul. Okrężna 16, 44-100 Gliwice Manufacturing plant: Rigips-Stawiany Factory

Szarbków 73, 28-400 Pińczów

System or systems of assessment and verification of constancy of performance:

System 3

Notified body: Building Research Institute (ITB), No. 1488

5. Harmonised standard:

PN-EN 520+A1:2012 Gypsum plasterboards. Definitions, requirements and test methods.

6. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Shear strength (for stiffening timber-framed external walls and timber roof truss structures)	NPD	PN-EN 520+A1:2012
Reaction to fire (for an uncovered product)	A2-s1,d0	PN-EN 520+A1:2012
Water vapour permeability (for moisture diffusion control) $[\mu]$	10	PN-EN 520+A1:2012
Flexural strength longitudinal direction transverse direction	650 N 250 N	PN-EN 520+A1:2012
Impact resistance (in end-use conditions)	These properties depend on the system, and they are provided in the manufacturer's information at www.rigips.pl depending on the expected applications	PN-EN 520+A1:2012
Airborne sound insulation (in end-use conditions)		
Acoustic absorption (in end-use conditions)		
Thermal resistance (as thermal conductivity)	0.25 W/(mK)	PN-EN 520+A1:2012

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by: Piotr Świerczek, Production Manager (name and position) Szarbków, 10 September 2018 (place and date of issue)

(signature

